

DI-604



KEY FEATURES

- Cable/DSL modem Internet sharing
- Built-in 4-port Fast Ethernet switch
- WAN port supports dial-up mode to save ISP connection fee
- Virtual Private Network (VPN) pass-through support
- DMZ and Virtual Server Mapping support
- Access control and URL blocking capability
- Network Time Protocol support
- Web-based configuration setup
- SNMP agent & built-in MIBs for management on third-party platforms*

Cable/DSL Router With Built-in 4-Port Switch

The DI-604 D-Link Express EtherNetwork is a broadband Internet Gateway Router with a built-in 4-port Fast Ethernet Switch. Designed for the small office and home, this router lets you quickly and easily share DSL or cable modem Internet connection. With advanced security functions, the DI-604 gives you a cost-effective way to install a secure and fast network with bottleneck-free link to the outside world.

Features and benefits

Simplified, Cost-saving Broadband Internet Connection:

With the DI-604, you can share your broadband cable/DSL line with everybody in your office or home. This device automatically creates and assigns an IP number for each user, simplifying every one's logon operation. 4 built-in 10/100Mbps switch ports provide ready connection for workstations and servers, while saving you the cost and trouble of installing a separate Ethernet switch.

Network Security:

The DI-604 provides NAT protection for your office and home users from Internet intruders and hacker attacks, plus VPN passthrough for extra security. It blocks and redirects certain ports to limit the services that outside users can access your network. Virtual Server Mapping is used to re-task services to multiple servers. The DI-604 can be set to allow separate FTP, Web, and Multiplayer game servers

to share the same Internet-visible IP address while still protecting your servers and workstations from hackers.

Access Control:

The DI-604 includes a group of filters you can configure to provide very basic content blocking. You can prevent local IP addresses from accessing domains, IP addresses, MAC addresses, and URLs that you specify and you can even make the restrictions dependent on the time of day.

DMZ Host to Open Public Domain:

You can configure any of the built-in LAN ports to function as a DMZ port. A DMZ setting can be applied to a single client (such as a Web server) behind the router to fully expose it to the Internet and ensure complete Internet application compatibility even if the specific port is not known. This allows you to set up web sites and e-commerce business from your office while maintaining protection for the rest of your office LAN. It also allows you to configure the DI-604 for applications that require multiple connections, such as Dialpad or MSN Gaming Zone.

UPnP Enabled for Compatibility:

The DI-604 is designed for easy and robust connectivity among heterogeneous standards-based network devices. Computers can communicate directly with the DI-604 for automatic opening and closing of UDP/TCP ports to take full advantage of security provided without sacrificing functionality of on-line applications.

* Available in future release.

CPU

- AMIT SOC

WAN Interface

- RJ-45 10BASE-T/100BASE-TX port
- Supports DSL and cable modem connection
- Supports "Always-on" (bridged) and PPPoE for PPP connection on demand

LAN Interface

- 4 RJ-45 10BASE-T/100BASE-TX ports

Routed Packet Type

- IP packets

Routing Protocols & Methods

- RIP-1, RIP-2
- Static Routing
- Dynamic Routing

VPN Support

- L2TP pass-through
- IPSec pass-through

Internet Gateway Functions

- Network Address Translation (NAT)
- DHCP server (for automatic IP assignment)

Number of Virtual Server Mappings

- 10 entries

RFC Support

- RFC 0768 User Datagram Protocol
- RFC 0791 Internet Protocol
- RFC 0792 Internet Control Message Protocol
- RFC 0793 Transmission Control Protocol
- RFC 0821 Simple Mail Transfer Protocol
- RFC 0826 Ethernet Address Resolution Protocol
- RFC 1058 Routing Information Protocol
- RFC 1112 IGMP v1 (for UPNP and IAPP functions)
- RFC 1157 Simple Network Management Protocol
- RFC 1213 Management Information Base-II (MIB II)
- RFC 1332 PPP Internet Control Protocol
- RFC 1350 TFTP Protocol (Reversion 2)
- RFC 1514 Dynamic Host Configuration Protocol
- RFC 1631 IP Network Address Translator
- RFC 1661 Point-to-Point Protocol (PPP)

- RFC 1723 RIP-2 Carrying Additional Information
- RFC 1945 Hypertext Transfer Protocol HTTP/1.1 (subset)
- RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
- RFC 2132 DHCP Options and BOOTP vender Extensions
- RFC 2516 PPP Over Ethernet (PPPoE)

IP Number Self-identification

- Through DHCP client

Configuration & Management

- Web-based configuration
- SNMP agent with built-in MIB-II*
- UPnP support

Firmware Upgrade

- Through TFTP

Memory

- SDRAM: 4MBytes
- Flash: 256KBytes

Security

- PPP Authentication PAP, CHAP, MS-CHAP

©2007 D-Link India Ltd. All rights reserved.

Users' agree to indemnify, defend and hold D-Link harmless from and against all losses, expenses, damages, including reasonable costs and fees, arising out of or relating to any misuse by the Users of the Product or of the information or content provided in this document.

* Available in future release.

Firewall Features

- Access-list control
- Domain filtering
- URL filtering
- Packet filtering
- Ping of Death
- IP spoofing
- Intrusion detection
- Network access rules
- Log file of security events

BUILT-IN FAST ETHERNET SWITCH

Standards

- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet
- ANSI/IEEE 802.3 NWay auto-negotiation

Supported Functions

- Full/half duplex (per port)
- MDI/MDIX auto uplink (per port)
- Auto correction of twisted-pair Rx reverse polarity (per port)

Flow Control

- IEEE 802.3x Flow Control in full-duplex
- Back pressure in half-duplex

Transmission Method

- Store-and-forward

MAC Address Learning

- Automatic update

Physical & Environmental

- Diagnostic LEDs
 - Power/Status
 - WAN (Link/Activity)

- 1, 2, 3, 4 LAN ports (Link/Activity)
- Power Input
 - DC 5V 2.0A
 - Through external 100 - 240 VAC power adapter
- Dimensions
 - 142 x 108 x 31 mm (55.9 x 42.5 x 12.2 inches)
- Weight
 - 200 grams (1.44 lb.)
- Operating Temperature
 - 0 - 55 C (32 - 131 F)
- Humidity
 - 95% maximum non-condensing
- EMI Certification
 - FCC Class B
 - CE Class B
 - C-Tick

Please specify one of the following after the model number:

- DI-604/A Includes US standard AC power adapter
- DI-604/B Includes UK standard AC power adapter
- DI-604/E Includes EU standard AC power adapter
- DI-604/CN Includes China standard AC power adapter
- DI-604/N Includes Australia standard AC power adapter
- DI-604/U Includes no AC power adapter



Ordering Information:

DI-604

1 RJ-45 10BASE-T/100BASE-TX port (for ADSL/ cable modem connection)
4 RJ-45 10BASE-T/100BASE-TX switch ports

©2007 D-Link India Ltd. All rights reserved.

Users' agree to indemnify, defend and hold D-Link harmless from and against all losses, expenses, damages, including reasonable costs and fees, arising out of or relating to any misuse by the Users of the Product or of the information or content provided in this document.

* Available in future release.